

O No/SSPune/GSDA/Tech/LGW/7/IS/2024

Dated 8/08/2024

To,

Navnath Sathe,
Wadgaon Shinde, Havell
District Pune

Subject- Regarding Hydrogeological Survey at Gat no.514/2A of Village Wadgaon Shinde, Taluka Havell,
District Pune

Reference - 1. Your letter dated 05/08/2024

2. Hydrogeological Survey Challan dated 06/08/2024

With reference to the above subject hydrogeological survey was carried out at Gat no.514/2A of
Village Wadgaon Shinde, Taluka Havell, District Pune. At the time of hydrogeological survey Shri. Sathe the
applicant was present.

The details of Proposed site are as follows:

Name Of Village	Wadgaon Shinde
Co-Ordinates	18°37'56" N and 73°57'18.1" E
Elevation	489 m
Toposheet & Morpho Unit	47 F/14
WaterShed No.	BM 37
Category	Safe (As per Groundwater Assessment 2022-23)
Rock Type	Basalt
Aquifer (Water Bearing Zone)	Shallow Aquifer (Jointed / Fractured Basalt)

Location

The village Wadgaon Shinde is located in the Northeast direction of Pune City at a distance of 16.00 km. The area under study i.e., said Gat no. Gat no.514/2A are located Southwest direction of Village Wadgaon Shinde at around distance of 500 mt.

Geomorphology- The topography is a plateau. A gentle to medium slope is in the North-to-Northeast direction with second order streams originating and flowing towards west direction. Lineament at a distance of 1000 mt is present to the East direction of the site running through the perennial Indrayani River.

Geology- The area of village Wadgaon Shinde consists of different layers of Basalt and the thickness varies from 2.00 to 10.00 mt which are formed during the Upper Cretaceous to Lower Eocene period of Geological time scale.

The basalt is dark grey to black in color, fine to medium grained and medium jointed and fractured in nature. The geological/lithological data as per field observations in the surveyed area is as below.

Lithology	Brownish coarse-grained soil	0.00 – 1.00 mt
	Highly to moderately weathered basalt	1.00 – 6.00 mt
	Greyish black colored, fine to medium grained jointed fractured vesicular basalt	6.00 – 10.00 mt
	Greyish black colored compact Massive Basalt	Below 10.00 mt

Hydrogeological Conditions – At the surveyed area the soil thickness ranges from 0.00 to 1.00 mt the weathered basalt thickness varies from 1.00 to 6.00 mt, jointed and fractured vesicular basalt from 6.00 to 10.00 mt and from 10.00 followed by massive basalt. The entire area of the studied 514/2A is underlain by the basaltic flows of Upper Cretaceous to lower Eocene. Groundwater in the Deccan Trap occurs mostly in

the weathered and fractured, jointed vesicular parts till 10.00 mt bgl under unconfined conditions. There is a lineament which is towards the Northwest of the Bore well. The water bearing strata at deeper depths exists under semi-confined to confined conditions at the depth of about 20-30 mt. from the groundwater availability point of view, the area has moderate groundwater yielding potential zone.

The availability of groundwater depends largely on surface and subsurface geology, geomorphology, natural drainage pattern, depth of weathering, and the fractures present. Actual annual rainfall, groundwater extraction from other sources in the surrounding area is also the factor which controls and affects the availability of groundwater.

Observations - At the time of survey 1 Bore well was observed in center of applicant's gat number (Gat no 514/2A) and Gat no 514/1A. The existing borewell is perennial in nature. Groundwater, which is obtained from the existing bore well is used for drinking and domestic purposes and can meet the water requirement for a population of around 50 souls which is 1,26,000 lt/day for drinking and domestic demand of the in Gat no Gat no 514/2A


Sr. no	Source	Location	Dimensions		SWL	Pump	Water availability
		Sr.no/Gat.no	Depth	Dia	(summer)		
1	Bore well	Gat no. 514/1A	90 mt	150 mm	20 mt(R)	3 HP	Around 1,26,000 lt/day

Recommendations -

1. The category of the area as per the groundwater assessment 2022-23 is Safe, the available water should be strictly used for drinking and domestic purposes.
2. The groundwater quality should be analyzed twice in a year (pre and post monsoon) by the applicant from the water testing laboratory at his own cost. Also, water quality to be maintained hence RO is recommended.
3. To have sustainable groundwater, groundwater recharge from rainwater harvesting to the existing sources should be implanted so that groundwater will be available perennially.
4. The topographical, hydrogeological conditions and rainfall play an important role in fulfilling the requirement of drinking, domestic use. In view of sustainable groundwater for the drinking and domestic purpose the groundwater recharge through surface runoff and rainwater harvesting measures in a quantity equal to the extraction of groundwater from the existing sources is mandatory to the applicant.
5. In view of sufficient water requirements for drinking, domestic and irrigation use, it is strongly recommended that a minimum of 70% of the extracted ground water must be recycled and reused for further usage.
6. The rainwater harvesting structures should be implemented under the technical guidance of this office (GSDA Pune)
7. During the Scarcity period the Scarcity Rule of Maharashtra Groundwater (Development and Management) Act 2009 are mandatory to the applicant.

Surveyed by

Sujata K Sawale
Assistant Geologist


(Dnyaneshwar Dinkar Dhote)
Senior Geologist
Groundwater Surveys and Development Agency,
Pune